

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: NanoPhos_GA_27072018-002

Product name SurfaPore T

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use stain protection and water proofing for marbles

1.3. Details of the supplier of the safety data sheet

Name NANOPHOS S.A.

Full address Technological & Science Park

District and Country 19 500 Lavrio (Greece)

Greece

Tel. +30 22920 69312 Fax +30 22920 69303

e-mail address of the competent person

responsible for the Safety Data Sheet iarabatz@NanoPhos.com

Product distribution by: loannis Arabatzis

1.4. Emergency telephone number

For urgent inquiries refer to +30 22920 69312

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin sensitization, category 1 H317 May cause an allergic skin reaction.

Hazardous to the aquatic environment, chronic toxicity, H411 Toxic to aquatic life with long lasting effects.

category 2

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

NANOPHOS S.A.

SurfaPore T

Revision nr. 2

Dated 27/07/2018

Printed on 27/07/2018

Page n. 2/13





Signal words: Warning

Hazard statements:

H317 May cause an allergic skin reaction.H411 Toxic to aquatic life with long lasting effects.

EUH208 Contains:, N-(3-(Trimethoxysilyl)propyl)ethylenediamine

May produce an allergic reaction.

Precautionary statements:

P280 Wear protective gloves.

P273 Avoid release to the environment.

P391 Collect spillage.
P103 Read label before use.
P102 Keep out of reach of children.

P261 Avoid breathing fume / gas / mist / vapours / spray.

P101 If medical advice is needed, have product container or label at hand.

Contains: Silsesquioxanes, (3-(2-aminoethyl)amino propyl)methyl, methoxy-terminated

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

Silsesquioxanes, (3-(2-aminoethyl)amino propyl)methyl,

methoxy-terminated

CAS 145775-27-5 5 < x < 10 Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic

Chronic 1 H410 M=1

EC 604-492-3 INDEX -**METHANOL**

EC 200-659-6

CAS 67-56-1 0 > x < 3

Flam. Liq. 2 H225, Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3

H331, STOT SE 1 H370

INDEX 603-001-00-X

Revision nr. 2 NANOPHOS S.A. Dated 27/07/2018 Printed on 27/07/2018 SurfaPore T Page n. 3/13

N-(3-

(Trimethoxysilyl)propyl)ethylenedi

amine

CAS 1760-24-3

0 < x < 1

Acute Tox. 4 H332, Eye Dam. 1 H318, Skin Sens. 1 H317

EC 217-164-6

INDEX -

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

NANOPHOS S.A.	Revision nr. 2
	Dated 27/07/2018
SurfaPore T	Printed on 27/07/2018
	Page n. 4/13

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

FRA JORF n°0109 du 10 mai 2012 page 8773 texte n° 102 France

GBR United Kingdom EH40/2005 Workplace exposure limits

ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012 **GRC** Ελλάδα OEL EU

Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

NANOPHOS S.A. Revision nr. 2 Dated 27/07/2018 Printed on 27/07/2018 Page n. 5/13 Page n. 5/13

TLV-ACGIH

ACGIH 2018

METHANOL							
Threshold Limit Valu	ıe						
Туре	Country	TWA/8h		STEL/15min			
		mg/m3	ppm	mg/m3	ppm		
VLEP	FRA	260	200	1300	1000	SKIN	
WEL	GBR	266	200	333	250	SKIN	
TLV	GRC	260	200	325	250		
OEL	EU	260	200			SKIN	
TLV-ACGIH		262	200	328	250		

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

NANOPHOS S.A.	Revision nr. 2 Dated 27/07/2018
Surfapore I	Printed on 27/07/2018 Page n. 6/13
	·

SECTION 9. Physical and chemical properties

liquid

9.1. Information on basic physical and chemical properties

Colour yellowish Odour imperceptible Odour threshold Not available рΗ Melting point / freezing point Not available Initial boiling point Not available Boiling range Not available > 60 °C Flash point Evaporation rate Not available Not available Flammability (solid, gas) Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Upper explosive limit Not available Vapour pressure Not available Vapour density Not available Relative density 1.00±0.05 kg/L Solubility Not available Partition coefficient: n-octanol/water Not available Auto-ignition temperature Not available Decomposition temperature Not available 2 mPa.s Viscosity Explosive properties Not available Oxidising properties Not available

9.2. Other information

VOC (Directive 2010/75/EC): 1,60 % - 16,00 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

Appearance

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

NANOPHOS S.A.	Revision nr. 2 Dated 27/07/2018
Surrapore I	Printed on 27/07/2018 Page n. 7/13
	age in 1710

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

METHANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

METHANOL

The minimum lethal dose for humans by ingestion is considered to be in the range from 300 to 1000 mg/kg. Ingestion of 4-10 ml of the substance may cause permanent blindness in adult humans (IPCS).

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

>2000 mg/kg

LD50 (Dermal) of the mixture:

>2000 mg/kg

N-(3-(Trimethoxysilyl)propyl)ethylenediamine

LD50 (Oral) 7,669 mg/kg

LC50 (Inhalation) 597 mg/l

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

NANOPHOS S.A. Revision nr. 2 Dated 27/07/2018 Printed on 27/07/2018 Page n. 8/13

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

May produce an allergic reaction. Contains: N-(3-(Trimethoxysilyl)propyl)ethylenediamine

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment. 12.1. Toxicity

Silsesquioxanes, (3-(2-aminoethyl)amino propyl)methyl, methoxy-terminated EC50 - for Crustacea

1 mg/l/48h DAPHNIA

12.2. Persistence and degradability

METHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

Revision nr. 2 NANOPHOS S.A. Dated 27/07/2018 Printed on 27/07/2018 SurfaPore T Page n. 9/13

12.3. Bioaccumulative potential

METHANOL

Partition coefficient: n-octanol/water -0,77 **BCF** 0,2

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, 3082

ADR / RID:

In accordance with Special

Provision 375, this product, when is packed in receptacles of a capacity

5Kg or 5L, is not submitted to ADR provisions.

IMDG: In accordance

with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity 5Kg or 5L, is not submitted to IMDG Code provisions.

NANOPHOS S.A. Revision nr. 2 Dated 27/07/2018 Printed on 27/07/2018 Page n. 10/13

IATA: In accordance

with SP A197, this product, when is packed in receptacles of a capacity 5Kg or 5L, is not submitted to IATA

5Kg or 5L, is not submitted to IATA dangerous goods regulations.

14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Silsesquioxanes, (3-(2-aminoethyl)amino

propyl)methyl, methoxy-terminated)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Silsesquioxanes, (3-(2-aminoethyl)amino

propyl)methyl, methoxy-terminated)

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Silsesquioxanes, (3-(2-aminoethyl)amino

propyl)methyl, methoxy-terminated)

14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9

IMDG: Class: 9 Label: 9

IATA: Class: 9 Label: 9



14.4. Packing group

ADR / RID, IMDG, III

IATA:

14.5. Environmental hazards

ADR / RID: Environmentally

Hazardous

IMDG: Marine Pollutant

IATA: Environmentally

Hazardous



14.6. Special precautions for user

ADR / RID: HIN - Kemler: 90

Special Provision: -

IMDG: EMS: F-A, S-F

IATA: Cargo:

Limited Tunnel
Quantities: 5 restriction
L code: (-)

Limited

Quantities: 5

-. .

Maximum Packaging quantity: 450 instructions:

964

NANOPHOS S.A.		Revision nr. 2 Dated 27/07/2018		
SurfaPore T		rinted on 27/07/2018 age n. 11/13		
Pass.:	Maximum quantity: 450	Packaging instructions:		
Special Instructions:	L A97, A158,	964		

A197

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>

Point 3

Contained substance

Point 69 METHANOL

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

NANOPHOS S.A. Revision nr. 2 Dated 27/07/2018 Printed on 27/07/2018 Page n. 12/13

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2 Flammable liquid, category 2
Acute Tox. 3 Acute toxicity, category 3

STOT SE 1 Specific target organ toxicity - single exposure, category 1

Acute Tox. 4 Acute toxicity, category 4

Eye Dam. 1 Serious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2

Skin Sens. 1 Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs.

H332 Harmful if inhaled.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

I FGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit

NANOPHOS S.A.	Revision nr. 2
	Dated 27/07/2018
SurfaPore T	Printed on 27/07/2018
	Page n. 13/13

- VOC: Volatile organic Compounds
- · vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
 The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 11 / 12 / 13 / 14.